



永华机械
YONG HUA MACHINERY

● Scraper Conveyor

Scraper Conveyor(also name chain conveyor) have large conveying capacity, simple structure, convenient maintenance, low cost, highly optimized for general use etc. Widely used in mining, metallurgy, coal, transport, hydropower and other departments for conveying bulk material or formed articles. According to the requirements of the transportation process, it can be single conveyor, also can be many sets of combination or combined with other conveyor, turn into a horizontal or inclined conveying system. Work environment is generally -25°C-200°C, special environment, should adopt the corresponding protection measures. Conveying density is 500-5500kg/ m³ of various materials.

Technical Parameters

Type	Belt Length (m) / Power (kw)			Speed (m/s)	Capacity (t/h)
B415	≤12/2.2	12-20/2.2-4	20-25/3.0-7.5	1.25-2.0	10-20
B500	≤12/3	12-20/3-5.5	20-30/5.5-7.5	1.25-2.0	30-50
B650	≤12/4	12-20/4-5.5	20-30/5.5-11	1.25-2.0	50-80
B800	≤10/4	10-15/4-5.5	15-30/5.5-15	1.25-2.0	80-100
B1000	≤10/5.5	10-20/5.5-11	20-40/11-22	1.25-2.0	120-200
B1200	≤10/7.5	10-20/7.5-15	20-40/15-30	1.25-2.0	200-380

● Photo of Scraper Conveyor





Contact: Alakay Email: alakay51@gmail.com
Yonghua Machinery Manufacturing Co., Ltd

<http://www.cnmachine.pw>